



산업용 무.선.통.신.서.버

Model : DWS-4000GE



**완벽한 전파 이중화를 구현한
산업용 무선랜 시스템**

REDUNDANT WIRELESS COMMUNICATION SYSTEM



Specification	DWS-4000GE
Basic Features	IEEE 802.11abg 11/54Mbps Wireless Interface 2.4GHz & 5GHz Dual-Band Mixed Channel Redundant Roaming Support Wired to Wireless TCP/IP Bridging and Routing Support Seamless Real-Time Roaming Support DATA and VIDEO Transmission Support Dual Antenna Port Included
Hardware Features	Intel PENTIUM-III 1GHz CPU, Industrial Computer 256MB DRAM, DUAL USB Port Flash-DISK 32MB Firmware
Wired Interface / LAN	Ethernet 10/100Mbps, RJ-45, Auto-Mid-X
Wireless Interface / WLAN	IEEE 802.11abg 11/54Mbps, Dual Antenna Port
Dimensions	218mm(W) x 200mm(H) x 95mm(D) / Wall-Mount
Power Supply (Included)	85~265VAC, 47~63Hz Input, 70W Output, 0~60 °C Operating Temperature, 274,000 Hours MTBF
Temperature	0-60 degrees Celsius with Cooler , Optional: Thermoelectric-Cooler
Humidity	95%/Max relative humidity

